

1x1 foot weatherproof soft light LED panel full R+G+B+W+CW with wireless control


Natural soft light color 5LED panel. Weatherproof IP54 rated. High color reproduction. High SSI, TLCI & CRI (96). Perfect skin tones and real colors. Robust, lightweight, low-carbon aluminum body. Totally silent fanless operation. High efficiency: 100% output even with batteries. Available V-lock / Gold mount. DMX-RDM, LumenRadio CRMX, Wi-fi Artnet and Bluetooth.

[More info](#)

[Website](#)




1. Accessories mounting plate
2. Light power buttons
3. Digital display
4. Up and down scroll buttons
5. Enter / +/- Adjustment buttons
6. 3200K / 5600K quick access buttons
7. Back button
8. Mode selection / Lock buttons
9. XLR-5 DMX-RDM In & Out connector
10. Main power switch
11. XLR-3 DC In connector
12. Mini USB connector



SPECIFICATIONS

COLOUR TEMPERATURE	Continuously adjustable from 2500K to 10000K
GREEN-MAGENTA	Continuously adjustable from full minusgreen to full plusgreen
COLOR SPECTRUM	Full color spectrum R+G+B+W+CW with hue, saturation, and base colortemperature control
CONTROL COLOR MODES	CCT, HSI, RGB, Gels and Effects base Kelvin white light can be set combined with any color
LIGHT INTENSITY	Dimmable 0 to 100, smooth and flicker-free
LOCAL CONTROL	With 8x shock resistant buttons and color display
WIRE CONTROL	DMX-RDM with XLR-5 in connector
WIRELESS CONTROL	DMX-RDM with LumenRadio, CRMX Wi-Fi Art-Net + VELVET Goya App, Bluetooth
TLCI INDEX	96 at 3200K and 97 at 5600K
PHOTOMETRICS	4591 lux / 423 fc at 1m / 3 feet 656 lux / 61 fc at 3m / 10 feet
BEAM ANGLE	115°
DIMENSIONS	453x318x92mm / 17.8x12.5x3.6 inches
WEIGHT	4.4 kg / 9.7 lbs (panel) 4.9 kg / 10.8 lbs (panel + yoke)
POWER DRAW	112W (0.47A at 220VAC — 1.0A at 110VAC)
POWER SUPPLY	12-35V DC (XLR3). VLock Gold mount battery 90-264V AC 50/60Hz
LED RATED LIFE	More than 50.000 hours
POWER CONNECTION	Neutrik PowerCon TRUE1 TOP In connector
OUTPUT FREQUENCY	2000 fps
OPERATION TEMPERATURE	From -20°C to +40°C
COOLING	Silent and fan-free pasive cooling
PROTECTION	IP54 weatherproof, indoor or outdoor use
VELVET LED TECHNOLOGY	Selected BIN LED core unit + optic diffuser + CPU software control
RIGGING OPTIONS	Aluminum yoke with 16mm baby receptacle combined with 28mm junior pin, center ball-head mount, multiple 1/4"- 20 rigging points, pole operated yoke.
QUICK MOUNTING ACCESSORIES	Foldable SnapBag, foldable Snapgrid, removable barn doors, cordura case, hard case
CONSTRUCTION & FINISH	Fixture and yoke made of black powdercoated extruded and sheet aluminum

WIRE VIEW



PHOTOMETRICS

